



Z & C PERLINS

Both ZED and CEE sections may be subject to minimum rolling quantities, minimum and maximum lengths.

Most stocks of purlins are kept in unpunched conditions and in these 3 lengths. 6.1m, 7.62m & 9.14m.

Purlins can be punched with no additional charges,

NOTE: some dimensions may vary from each manufacturer.

CODE	Z & C THICKNESS	Z & C DEPTH	TOP Z FLANGE	BOTTOM Z FLNGE	Z RETURN	TOP & BOTTOM C FLANGE	C RETURN	MASS (KG/M)
Z/C10010	1.0	102	53	49	12.5	51	12.5	1.78
Z/C10012	1.2	102	53	49	12.5	51	12.5	2.10
Z/C10015	1.5	102	53	49	13.5	51	13.5	2.62
Z/C10019	1.9	102	53	49	14.5	51	14.5	3.29
Z/C15012	1.2	152	65	61	15.5	64	14.5	2.89
Z/C15015	1.5	152	65	61	16.5	64	15.5	3.59
Z/C15019	1.9	152	65	61	17.5	64	16.5	4.51
Z/C15024	2.4	152	65	60	19.5	64	1.5	5.70
Z/C20015	1.5	203	79	74	15.0	76	15.5	4.49
Z/C20019	1.9	203	79	74	18.5	76	19.0	5.74
Z/C20024	2.4	203	79	73	21.5	76	21.0	7.24
Z/C25019	1.9	254	79	74	18.0	76	18.5	6.50
Z/C25024	2.4	254	79	73	21.0	76	20.5	8.16
Z/C30024	2.4	300	100	93	27.0	96	27.5	10.09
Z/C30030	3.0	300	100	93	31.0	96	31.5	12.76
Z/C35030	3.0	350	129	121	30.0	125	30.0	15.23